

SAFETY DATA SHEET

Section 1. Product Identification

Product identifier Dynaplast® Base Alpha, Dynaplast® Alpha Q/S, Dynaplast® Alpha Q/S Buff,

Dynaplast® HS, Dynaplast® FS, Dynaplast® GRG Gypsum Cement, Dynaplast® GRG XL, Dynaplast® OCG 60, Dynaplast® OCG 120, Dynaplast® DS712, Dynaplast® DS712 Buff, DynaPlast® EZ White, DynaPlast® Orthopedic Alpha POP 13-18,

DynaPlast® Ortho POP 4-8.

Other means of identification

SDS number ACG 2001

Additional Products Pottery Plaster, Moulding Plaster, Moulding Plaster, 5/5, 15 min Moulding Plaster, 20

min Moulding Plaster, 30 min Moulding Plaster, Quick-Set Plaster of Paris, Slow-Set

Plaster of Paris, Lab Dental Plaster Q/S, and Dental Plaster 1530.

Synonyms Plaster of Paris

Recommended useIndustrial use applications, Ceramics, and modeling. **Recommended Restrictions**Use in accordance with manufacturer's recommendations.

Manufacturer/Importer/Supplier/Distributor information

Company name Arcosa Specialty Materials
Address 1550 Double Drive

Norman, OK 73069 **Telephone** 1-800-624-5963

Website www.ArcosaSpecialtyMaterials.com

Emergency phone number 1-800-624-5963

	Section 2. Hazard(s) Identification				
Emergency Overview					
	or eye irritation. A single exposure will not result in serious adverse health effect. Prolong				
	contact with the product may result in abrasions to the skin or irritation of the eyes. Prolonged				
	inhalation of the dust may irritate the respiratory tract.				
Physical hazards	Not classified				
Health Hazards	Not classified				
Acute:					
Eyes	Contact can cause mechanical irritation of eyes. If burning, redness, itching, pain or other symptoms persist or develop, consult physician. Eye irritation Category 2, subcategory 2B.				
Skin	This material hardens and slowly become shot when mixed with water. However, direct				
	prolonged or repeated contact with the skin may cause irritation. Rubbing of this product				
	against the skin can result in abrasions. Rinse with water until free of material to avoid				
	abrasions, and then wash skin thoroughly with mild soap and water. May dry skin. Mild Skin				
	Irritation Category B.				
	Inhalation of dusts from this product may irritate the nose, throat, lungs, and upper respiratory				
	tract. Persons exposed to large amounts of this dust may be forced to leave area because of				
	nuisance conditions such as coughing, sneezing, and nasal irritation. Labored breathing may				
	occur after excessive inhalation. If respiratory symptoms persist, consult physician.				
Ingestion	Harmful if swallowed. Plaster of Paris is non-toxic, however, ingestion of a sufficient quantity				
	could lead to mechanical obstruction of the gut, especially the pyloric region. See Section 4.				
Chronic:					
Inhalation	Gypsum displays no specific toxic properties. Prolonged and repeated exposure to respirable				
	crystalline silica can result in lung disease (i.e. silicosis) and lung cancer. Silicosis increases the				
	risk of tuberculosis. Studies have shown various autoimmune and chronic kidney diseases in				
	workers exposed to respirable crystalline silica. Some studies show and increased incidence of				
	chronic bronchitis and emphysema in workers exposed to crystalline silica.				
Skin	Dermatitis.				

SDS ID: ACG 2001 Revision date: 2/13/2025 Page **1** of **5**



Environmental hazards OSHA defined hazards

Not Classified. Not Classified.

Label elements





Signal word

Danger

Hazard statement

Harmful if swallowed. Causes eye and skin irritation. May cause allergy or asthma symptoms

or breathing difficulties if inhaled.

Precautionary statement

Prevention

Avoid breathing dust. Wash hands thoroughly after handling. Wear protective gloves. Wear respriatory protection. Do not eat, drink, or smoke when using this product. Contact lenses

should not be worn while working with Plaster of Paris.

Response

If eye irritation persists, if skin irritation occurs, or if experiencing respiratory symptoms: Get

medical advice/attention. If swallowed: Call a doctor if you feel unwell.

Storage

Store as inidated in Section 7.

Disposal

Dispose of in accordance with local, state, and federal regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Section 3. Composition/Information on Ingredients					
Mixtures					
Chemical name	CAS number	%			
Calcium Sulfate Hemihydrate	26499-65-0	>95			
(Plaster of Paris)					
Silicon Dioxide (Crystalline Silica)	14808-60-7	< 0.025			

Composition comments

All concentrations are in percent by weight unless ingredient is a gas.

	Section 4. First-Aid Measures			
Eye contact	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and			
	easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention			
Skin contact	1 7 1 1			
	first aid instruction on label. If skin irritation occurs: Get medical advice/attention. Take off			
	contaminated clothing and wash it before reuse.			
Inhalation	If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.			
	If experiencing respiratory symptoms: Call a doctor.			
Ingestion	If swallowed: Call a doctor if you feel unwell. Rinse mouth. Unlikely to occur, but may cause gastric disturbances if swallowed. Plaster of Paris is non-toxic; however, ingestion of a sufficient quantity could lead to mechanical obstruction of the gut, especially the pyloric region. Get medical			
	attention immediately. The use of diluents is controversial and neutralization is contraindicated.			
Target Organs:	Eyes, skin and respiratory system.			
Medical Conditions which	Pre-existing upper respiratory and lung diseases such as, but not limited to, bronchitis, emphysema,			
may be aggravated	and asthma.			
Primary Routes of entry:	Inhalation, eyes and/or skin contact, ingestion.			

SDS ID: ACG 2001 Revision date: 2/13/2025 Page **2** of **5**



	Sect	ion 5. Fire and Explosion Hazard Data			
Flash Point		ombustible			
Auto-Ignition	Not ap	plicable.			
Flammable limit		plicable.			
Fire Extinguishing Media		tinguishing media appropriate for surround	ding fire.		
Special Fire-fighting Procedures Wear proper personal protective equipment as listed in Section 8.					
Hazardous combustion proce					
Explosion Hazards	None l	known.			
		ction 6. Accidental Release Measures			
Methods and materials for		y sweeping or vacuum. Avoid creating exc			
containment and cleaning up	and a mask be worn while cleaning the spill. If already mixed with water, scrape up and p container. Wear appropriate protective equipment as described in Sections 7 & 8.				
Environmental precautions		aterial in accordance with all applicable fe			
	disposed as ar	n inert solid in a landfill. Slurry may plug o	drains.		
		Section 7. Handling and Storage			
Precautions for safe		with skin and eyes. Do not breathe dust. U			
handling		t mask or filtering face piece is recomme			
		sposure limits may be exceeded. When using or smoking.	ng, do not eat or drink. Wash hands befo		
Conditions for sofe storage		each of children. Keep the container tightl	ly alocad and dry Store in a acyarad d		
Conditions for safe storage, including an		1	•		
including an	climate controlled area, away from incompatibles listed in Section 10.				
	Section	•			
incompatibilities Occupational exposure limits	s	8. Exposure Controls/Personal Protection			
incompatibilities Occupational exposure limits US. OSHA table Z-1 Limits 1	s for Air Contamii	8. Exposure Controls/Personal Protectionants (29 CFR 1910.1000	on		
incompatibilities Occupational exposure limits US. OSHA table Z-1 Limits 1 Components	s for Air Contamii Type	8. Exposure Controls/Personal Protectionants (29 CFR 1910.1000 Value	on Form		
incompatibilities Occupational exposure limits US. OSHA table Z-1 Limits 1 Components Plaster of Paris	s for Air Contamii Type PEL	8. Exposure Controls/Personal Protection nants (29 CFR 1910.1000 Value 5 mg/m3	Form Respirable.		
Occupational exposure limits US. OSHA table Z-1 Limits f Components Plaster of Paris Crystalline Silica	s for Air Contamin Type PEL TWA	8. Exposure Controls/Personal Protectionants (29 CFR 1910.1000 Value	on Form		
incompatibilities Occupational exposure limits US. OSHA table Z-1 Limits f Components Plaster of Paris Crystalline Silica	s for Air Contamin Type PEL TWA	8. Exposure Controls/Personal Protection nants (29 CFR 1910.1000 Value 5 mg/m3	Form Respirable.		
incompatibilities Occupational exposure limits US. OSHA table Z-1 Limits 1 Components Plaster of Paris Crystalline Silica US. ACGIH Threshold Limit	s for Air Contamin Type PEL TWA t Values Type	8. Exposure Controls/Personal Protectionants (29 CFR 1910.1000 Value 5 mg/m3 5 mg/m3	Form Respirable. Respirable		
Occupational exposure limits US. OSHA table Z-1 Limits to Components Plaster of Paris Crystalline Silica US. ACGIH Threshold Limits Components Plaster of Paris	s for Air Contamin Type PEL TWA t Values Type TWA	8. Exposure Controls/Personal Protectionants (29 CFR 1910.1000 Value 5 mg/m3 5 mg/m3	Form Respirable. Respirable Form Inhalable fraction.		
incompatibilities Occupational exposure limits US. OSHA table Z-1 Limits 1	s for Air Contamin Type PEL TWA t Values Type	8. Exposure Controls/Personal Protectionants (29 CFR 1910.1000 Value 5 mg/m3 5 mg/m3	Form Respirable. Respirable		
Occupational exposure limits US. OSHA table Z-1 Limits 1 Components Plaster of Paris Crystalline Silica US. ACGIH Threshold Limit Components Plaster of Paris Crystalline Silica	s for Air Contamin Type PEL TWA t Values Type TWA TWA	8. Exposure Controls/Personal Protectionants (29 CFR 1910.1000 Value 5 mg/m3 5 mg/m3 Value 10 mg/m3 0.025 mg/m3	Form Respirable. Respirable Form Inhalable fraction.		
Occupational exposure limits US. OSHA table Z-1 Limits for the Exposure limits US. OSHA table Z-1 Limits for the Exposure limits Components US. ACGIH Threshold Limits Components Plaster of Paris Crystalline Silica US. NIOSH: Pocket Guide to Components	s for Air Contamin Type PEL TWA t Values Type TWA TWA TWA TWA TWA TWA Type	8. Exposure Controls/Personal Protectionants (29 CFR 1910.1000 Value 5 mg/m3 5 mg/m3 Value 10 mg/m3 0.025 mg/m3 rds Value	Form Respirable. Respirable Form Inhalable fraction. Respirable. Form		
Occupational exposure limits US. OSHA table Z-1 Limits to Components Plaster of Paris Crystalline Silica US. ACGIH Threshold Limits Components Plaster of Paris	for Air Contamin Type PEL TWA t Values Type TWA TWA TWA O Chemical Haza Type TWA	8. Exposure Controls/Personal Protectionants (29 CFR 1910.1000 Value 5 mg/m3 5 mg/m3 Value 10 mg/m3 0.025 mg/m3 rds Value 5 mg/m3	Form Respirable. Respirable Form Inhalable fraction. Respirable.		
Occupational exposure limits US. OSHA table Z-1 Limits to Components Plaster of Paris Crystalline Silica US. ACGIH Threshold Limits Components Plaster of Paris Crystalline Silica US. NIOSH: Pocket Guide to Components Plaster of Paris	s for Air Contamin Type PEL TWA t Values Type TWA TWA TWA TWA TWA TWA Type	8. Exposure Controls/Personal Protectionants (29 CFR 1910.1000 Value 5 mg/m3 5 mg/m3 Value 10 mg/m3 0.025 mg/m3 rds Value	Form Respirable. Respirable Form Inhalable fraction. Respirable. Form		
Occupational exposure limits US. OSHA table Z-1 Limits for the Exposure limits US. OSHA table Z-1 Limits for the Exposure limits Components US. ACGIH Threshold Limits Components Plaster of Paris Crystalline Silica US. NIOSH: Pocket Guide to Components	Type PEL TWA t Values Type TWA TWA Chemical Haza Type TWA TWA Ventilate to 1	8. Exposure Controls/Personal Protectionants (29 CFR 1910.1000 Value 5 mg/m3 5 mg/m3 Value 10 mg/m3 0.025 mg/m3 rds Value 5 mg/m3	Form Respirable. Respirable Form Inhalable fraction. Respirable. Form Respirable. s of the individual ingredients. Gener		

SDS ID: ACG 2001 Revision date: 2/13/2025 Page **3** of **5**



may be exceeded. Consult with respirator manufacturer to determine respirator selection, use, and limitations.

C 4 · 0	DI		I D
Section 9.	Physical a	na Chemica	I Properties

White **Appearance** Powder/Solid. Physical state **Melting Point** Not applicable. Not applicable. **Freezing Point**

Odor Low.

Odor threshold Not determined. Flash point Non-combustible. Flammability limits Not applicable.

Solubility (in water) (g/100g) 0.15%

Initial boiling point Not applicable **Boiling Range** Not applicable. 2.6-3.0 Specific gravity

рH

Hardening time

25-120 minutes Vapor pressure Not applicable. Vapor density Not applicable.

Auto-ignition temperature None.

Evaporation rate Not applicable. Viscosity Not applicable. Upper flammability limit Not determined. Lower flammability limit Not determined. **Decomposition temp** 1451°C/2642°F

Section 10. Chemical Stability and Reactivity

Reacts with water and produces large amounts of heat (normal condition of use). Conditions of reactivity

Chemical stability Stable at normal storage conditions and temperature.

Conditions to avoid Water, high humidity, and acids.

Hazardous decomposition products Stable at normal storage conditions and temperature.

Hazardous polymerization None known.

Section 11. Toxicological Information

Information on likely routes of exposure

Acute effects The acute oral toxicity study [OECD TG 420] of calcium sulfate dihydrate showed that this

chemical did not cause any changes and there was no evidence of germ cell mutagenicity.

Chronic effects Crystalline Silica: Exposures to respirable crystalline silica are not expected during the normal use

of this product; however, levels must be determined by in-house workplace hygiene testing.

Section 12. Ecological Information

There are no known causes from this product that would harm the Ecology. **Ecotoxicity**

Section 13 Disposal Considerations

SDS ID: ACG 2001 Revision date: 2/13/2025 Page 4 of 5



Disposal procedure

Dispose of material in accordance with all applicable federal, state and local regulations. Can be disposed as an inert solid in a landfill. Slurry may plug drains. Do not dispose of directly in waterways or sewers.

Section 14. Transport Information

Department of Transportation (DOT)This product is not regulated as a hazardous material by the United States

Requirements (DOT) transportation regulations.

Canadian Transportation of dangerous goods Not regulated as dangerous goods.

UN# None, Not regulated as dangerous goods.

ADNR None.

RID/ADR: Not classified.

Environmental hazards None.

Annex II of MARPOL 73/78 Not applicable.

International bulk chemical codeNot applicable.

Section 15 Regulatory Information

U.S. EPA's Toxic Substance Control Act Chemical Substance Inventory

Not listed as reportable quantity or regulated quantity in SARA Title III Sections 302, 304, and 313. CAA Section 112® Regulated Chemicals for Accidental Release

Prevention, CERLA Hazardous Substances, and RCRA Hazardous Waste.

Canadian Controlled Product

Regulations

Crystalline Silica: IDL* Item #1406 Classification: D2A

European Union Directive 67/548/EEC (Annex III and IV)

R36, R37, R38, S37, S3, S39, and S51.

*IDL Item: Canadian Hazardous Product Act Ingredient Disclosure List

** WHMIS: Workplace Hazardous Safety Information System

Section16 Other Information

16. Other Information, including date of preparation or last revision


Issue date March 04, 2015 Revision Date: February 13, 2025

Further information NFPA Ratings "

Health: 1 Flammability: 0 Physical hazard: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

NFPA ratings



Disclaimer:

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.

SDS ID: ACG 2001 Revision date: 2/13/2025 Page **5** of **5**